

Lucid Air 19" Wheel Graphics

Items you will need:

- Alcohol
- paper towel or microfiber cloth
- scissors
- squeegee or credit card

Instructions:

1. Clean car and wheels
2. Clean spokes with alcohol and paper towel
3. Trim decals so there is only one decal per sheet
4. Test the alignment of the decal on the wheel with the white release liner still attached. The corner of the L-shaped decal should align with the small spoke on the outside of the wheel. Once you are comfortable with the alignment, move on to the next step.
5. Remove the white release liner
6. Carefully align the graphic over the wheel without touching the surface. If it does touch gently pull it back off the wheel.
7. Align the corner of the graphic to the outside edge of the small spoke. When it is in the correct position gently touch it to the wheel and confirm alignment.
8. With only the corner touching, align the spoke part of the graphic that points to the center of the wheel. Adjust the position so the graphic covers all the bright silver areas on both sides. Once aligned apply pressure from the outside edge of the graphic pressing down the decal as you move towards the center. Applying the graphic in one area first then smoothing it out as you press it down to minimise air being trapped under the vinyl that will create bubbles. If you notice bubbles, peel the graphic up and re-apply.
9. Press the graphic from the corner along the outside of the wheel making sure to check for alignment so the outside exposed bright area of the rim has a consistent width.
10. Press down with a squeegee or credit card to remove all air and make sure the graphic is securely attached.
11. Remove clear transfer tape
12. If there is any adhesive left from the transfer tape you can remove it by using the transfer tape like a lint roller and pick up the adhesive or use alcohol with a microfiber cloth

www.ditzco.com

